

RAIN TEST CHAMBER (RN)



TECHNICAL DATA SHEET

Performance

Conform to IS 9000, JSS 55555, JIS D 0203, S 12063, IEC 60529 (IP), DIN 40050 IP 1 TO 9k & ISO 120653 IP 1 TO 9k

Is 9000 / Jss 55555

Rain spray nozzles as per IS 9000 / JSS 55555. total 8 nozzles, four nozzles at the top four corners inclined at 45 degree and 4nozzles in the center of each four sides. Pressure Gauges for each nozzle. Rotameter to monitor rate, Rotating Table.

Is 12063 / IEC 605239 (IP)

Oscillating pipe formed in to a semi-circle with nozzles as per IP. Rotating Table with 'T' slots.

JIS D 0203

Rotating nozzle and Rotating table as per JIS D 0203

*Drip Test, Jet Test & Immersion Test as per IEC 60529 (IP)
IP4K/6K/9K also available on request

STANDARD TEST SPACE

RN (IS 9000 / jss 55555)

MODEL	VOLUME (Litres)	W (MM)	D (MM)	H (MM)
RN-1750	1750	1200	1200	1200

RN (JIS)

MODEL	VOLUME (Litres)	W (MM)	D (MM)	H (MM)
RN-420	420	750	750	750
RN-1000	1000	1000	1000	1000

*Test Space can be provided as per customer requirement

*Appearance & Design of Chamber may vary depending on the internal dimensions